

6-EVF-12 (12V12AH/20HR)

LONG WAY 6-EVF-12 is one of the Deep Cycle battery of LONGWAY BATTERY..

This series adopts AGM technology, which has high safety & reliability, maintenance-free, high charging rate, low self-discharge, and long life.

Applications: Electric vehicles, Electric scooter, Electric wheel chair, Electric play car for children Sanitation vehicles and police patrol car etc.



Specifications: Designed according with the IEC60254-2014

12Volts (6 Cells per unit) Nominal Voltage

Nominal Capacity @25°C

20hr -rate (0.60A) 13.0Ah @ 1.75V per cell@25℃ (77°F) 10Hr-rate (1.10A) 12.0AH @ 1.75V per cell@25℃ (77°F) 5Hr-rate (2.04A) 11.2AH@1.70Vper cell@25℃ (77°F) 10.0AH@1.70Vper cell@25°C (77°F) 3Hr-rate(3.00A)

Weight Approx.3.55 \pm 3%kg(7.82 lbs)

Approx. 13.0mΩ full charged @25℃ Internal Resistance

Maximum Discharge Current 120A(3sec)

Operating Temperature Range Discharge: -20°C~50°C; Charge: 0°C~40°C

Storage: -20 ℃~40 ℃

Equalization and Cycle Service 14.40~15.0VDC/unit Average @ 25°C

Maximum Charging Current 3.60A F2

Terminal

Container Material ABS (UL 94-HB) & Flame Retardant (94-V0)

available upon request

Outer Dimensions

Self Discharge LONGWAY batteries can be stored for more than 6

months and the Self-discharge ratio less than 3%per month at 25℃.Please charge batteries before using

Terminal Type




IISO9001:2015 ISO14001:2015 ISO45001:2018 ISO50001:2011

APPLICATION STANDARDS

- ISO 7176-25 2013
- IEC 60254-1- 2005
- SAE J1495-2018
- UL1989 (MH46789)

Length:151 ± 1mm Width:98±1mm Height:93±1mm Total Height:99±2mm

Dimensions






Cycle Service Life

(Ah%) Capacity (100 ₽ Percentage 20 Numbers of Cycle (Times)

Capacity Retention Characteristic



Kaiying Power Supply & Electrical Equip Co., Ltd

Add: Laogang Industrial Area, Chengxiang Town , Anxi, Quanzhou City, Fujian Province , China

Tel: 0595-68782266 Fax: 0595-68782222 Web: www.longwaybattery.com Email: sales@longwaybattery.com KY-IOP-6-EVF-12 A0. February 2022