



General VRLA Battery

FM100G (2V100Ah)

The LONGWAY General Series 2V batteries (100-3000Ah) are designed and developed using AGM technology and valve controlled sealing technology. They can meet conventional performance requirements, with a designed float charging life of over 15 years. The valve controlled non-spillable structure design allows safe use in any direction and is certified by sea and air freight. The battery performance also meets international standards. such as IEC60896-2012, UL1989.etc.



General Feature

- High reliability, safe without leakage, can be used in any position
- Excellent recovery performance after deep discharge
- Environmentally friendly products.
Meet EU battery directive RoHS and REACH standards
- Maintenance free
- Widely applicable temperature range, can be used at -20 °C~60°C
- Low self-discharge rate. The average monthly self-discharge rate of the battery is less than 2.5%
(It is recommended to recharge after storage for 6 months or before use)


Applications

- Electrical power system
- Solar system
- Electrical test equipment
- Telecom & Network Equipment
- UPS, fire alarm & safe-protection
- Emergency lighting device; Alarm system
- Robots and control machines and other

Performance

Nominal Voltage	2V (1cell)
Capacity	@25°C
10hr Rate (10.0A)	93.0Ah @ to 1.75V/cell
5hr Rate (17.0A)	85.0Ah @ to 1.70V/cell
3hr Rate (25.0 A)	75.0Ah @ to 1.60V/cell
Weight	Approx (6.00±3%)kg (13.23lbs)
Internal Resistance	Approx 1.10mΩ fully charged @25°C
Maximum Discharge Current	400A(3sec)
Terminal	17
Operating Temperature Range	Discharge:-20°C~60°C; Charge:0°C~50°C Storage:-20°C~40°C
Container Material	ABS(UL94 HB)/UL94-V0 Optional

Dimensions



Length	171mm	6.73inch
Width	72mm	2.83inch
Height	205mm	8.07inch
Total height	210mm	8.27inch

Battery use

Cycle use

1. Limit the initial charging current to no more than 25A
2. Keep charging voltage at 2.40-2.50V/unit.and continue charging at least 3 hours after the charging current reduces to2.0A to ensure full charge
3. The compensation coefficient of charging voltage and temperature is -5mv/cell/°C

Float use

1. Limit the initial charging current to no more than 25A
2. Keep charging voltage at 2.25-2.30V/unit.When the voltage reaches the constant voltage,the current gradually decreases until the battery is fully charged and continues to charge
3. The compensation coefficient of charging voltage and temperature is -3mv/cell/°C




Kaiying Power Supply & Electrical Equip Co., Ltd Email: sales@longwaybattery.com
 Tel:0595-68782266 Fax:0595-68782222 Website: <http://www.longwaybattery.com>
 Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
 KY-IOP-LW2-100 B0. May 2023

Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery. Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information.




General VRLA Battery FM100G (2V100Ah)

Floating Charging Life VS Temperature




Floating Charging Characteristics Diagram



Cycle Life




Cycle charging characteristic diagram



Temperature and capacity characteristics



Self-discharge characteristic



Constant current characteristics(A,25°C)

F.V/TIME	15min	30min	60min	2h	3h	5h	8h	10h	20h	100h
1.60	135	105	56.0	37.0	26.7	18.8	13.2	10.7	5.33	1.27
1.65	126	103	52.1	36.9	26.6	18.7	13.1	10.6	5.32	1.27
1.70	130	101	53.8	36.7	26.4	18.6	13.1	10.6	5.28	1.26
1.75	126	97.7	52.1	36.5	26.3	18.5	13.0	10.5	5.27	1.25
1.80	123	95.8	51.1	35.8	25.8	18.1	12.4	10.5	5.25	1.25

Constant power discharge characteristic (W,25°C)

F.V/TIME	15min	30min	60min	2h	3h	5h	8h	10h	20h	100h
1.60	243	194	107	68.2	52.7	37.4	26.3	21.3	10.7	2.54
1.65	226	190	100	67.8	52.5	37.2	26.2	21.3	10.6	2.53
1.70	233	186	103	67.5	52.2	37.0	26.1	21.1	10.6	2.52
1.75	226	181	100	67.2	51.9	36.8	25.9	21.1	10.5	2.51
1.80	222	177	97.8	65.8	50.9	36.1	24.6	21.0	10.5	2.50



Kaiying Power Supply & Electrical Equip Co., Ltd
 Tel:0595-68782266 Fax:0595-68782222
 Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
 KY-IOP-LW2-100 B0. May 2023

Email: sales@longwaybattery.com

Website: <http://www.longwaybattery.com>

Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery. Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information.